



MGU3.524.18



MGU3.525.18

## Movement and presence detectors

	300 W detector	2300 W detector
Colour	2 modules	2 modules
<input type="checkbox"/> white	<b>MGU3.524.18</b>	<b>MGU3.525.18</b>
<input type="checkbox"/> ivory	<b>MGU3.524.25</b>	<b>MGU3.525.25</b>

- Adjustable disconnection time and brightness
- Optional switching of the load connected to the control switch using conventional auxiliary push-buttons



MGU3.524.XX



MGU3.525.XX

## Load table

MGU3.524.XX	MGU3.525.XX		
300 W	2300 W		230 V AC incandescent lamps
300 W	2000 W		230 V AC halogen lamps
	1050 VA		ELV halogen lamps with wire-wound transformer (non toroidal)
	1150 VA		ELV halogen lamps with electronic transformer
	2000 VA cos $\varphi \geq 0,9$		230 V AC fluorescent tube, $\Phi 26$ or $\Phi 38$ mm
	500 VA		230 V AC compact fluorescent lamps
	200 VA		230 V AC fans
300 W cos $\varphi \geq 0.95$	2300 W		230 V AC convectors
	200 VA		230 V AC contactors
		<b>Installation</b>	
		Parallel connection: max. 2 detectors for a load	
		Possibility of using up to 5 push-buttons in the surrounding area	